

CONSTRUCTION	<ul style="list-style-type: none"> ↗ 4 jack rings for comfortable transportation ↗ Metal runners for fork-lift transport and ground ventilation ↗ 4 handles for manual transport ↗ Gas struts prevent slamming of the lid ↗ Protective corners offer additional collision protection and stability ↗ Best-Point-Technology (joining process, the protective zinc coating is not damaged) 										
MATERIAL	<ul style="list-style-type: none"> ↗ Galvanized sheet steel S220 GD Z; 1.0241 and S250 GD Z; 1.0242 ↗ Surface: MB, hot-dip galvanized ↗ Trapezoidal sheet thickness: 0.8mm ↗ Profile thickness: 1.5mm or 2mm 										
OSB FLOOR	<ul style="list-style-type: none"> ↗ OSB/3 panel for use in structural applications in humid areas in accordance with EN 300 ↗ Panel thickness: 18mm ↗ Load bearing capacity: 500kg/m² ↗ Fully PMDI (formaldehyde free) glued, low-emission (E1) ↗ Guaranteed pest free (IPPC standard) ↗ European building material classification according to EN 13501-1: D - s2, d0 										
CRANE HANDLING	<ul style="list-style-type: none"> ↗ Up to 250kg permissible total weight 										
SNOW LOAD	<ul style="list-style-type: none"> ↗ 2.10kN/m² 										
SIZE/WEIGHT	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr style="background-color: #cccccc;"> <th colspan="2">WSB</th> </tr> </thead> <tbody> <tr> <td>Width external/internal (mm)</td> <td>1900/1770</td> </tr> <tr style="background-color: #cccccc;"> <td>Length external/internal (mm)</td> <td>700/570</td> </tr> <tr> <td>Height external/internal (mm)</td> <td>875/750</td> </tr> <tr style="background-color: #cccccc;"> <td>Weight (kg)</td> <td>105</td> </tr> </tbody> </table>	WSB		Width external/internal (mm)	1900/1770	Length external/internal (mm)	700/570	Height external/internal (mm)	875/750	Weight (kg)	105
WSB											
Width external/internal (mm)	1900/1770										
Length external/internal (mm)	700/570										
Height external/internal (mm)	875/750										
Weight (kg)	105										
DELIVERY	<ul style="list-style-type: none"> ↗ Assembled delivery 										
ACCESSORIES ONLY FOR THE WSB	<ul style="list-style-type: none"> ↗ 2 discus locks (simultaneous locking) with 2 keys each 										